LPS.

SAFETY DATA SHEET

1. Identification

Product identifier LPS® HDX

Other means of identification

Part Number 01005, 01055

Recommended use A degreaser designed to remove grease, oil, dirt and other residues from metal and other hard

surfaces near ignition sources.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Germ cell mutagenicity Category 2
Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. May

cause cancer. May cause drowsiness or dizziness.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Hazard(s) not otherwise

Dispose of contents/container in accordance with local/regional/national/international regulations.

classified (HNOC)

None known.

Supplemental information

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
1,1,2-trichloroethylene		79-01-6	90 - 100	

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

attendance.

Most important

symptoms/effects, acute and

delaved

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

Material name: LPS® HDX SDS US

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air (Components	Type	Value	Form	
Butanone (CAS 78-93-3)	PEL	590 mg/m3 200 ppm		
Camphor USP (CAS 76-22-2)	PEL	2 mg/m3		
Diphenyl Oxide (CAS 101-84-8)	PEL	7 mg/m3	Vapor.	
so amyl acetate (CAS 123-92-2)	PEL	1 ppm 525 mg/m3	Vapor.	
Turpentine (CAS 8006-64-2)	PEL	100 ppm 560 mg/m3		
*		100 ppm		
US. OSHA Table Z-2 (29 CFR 1910.1 Components	Type	Value		
1,1,2-trichloroethylene CAS 79-01-6)	Ceiling	200 ppm		
	TWA	100 ppm		
JS. ACGIH Threshold Limit Values Components	Туре	Value	Form	
1,1,2-trichloroethylene (CAS 79-01-6)	STEL	25 ppm		
	TWA	10 ppm		
Butanone (CAS 78-93-3)	STEL	300 ppm		
	TWA	200 ppm		
Camphor USP (CAS 76-22-2)	STEL	3 ppm		
	TWA	2 ppm		
Diphenyl Oxide (CAS 101-84-8)	STEL	2 ppm	Vapor.	
	TWA	1 ppm	Vapor.	
so amyl acetate (CAS 123-92-2)	STEL	100 ppm		
	TWA	50 ppm		
Turpentine (CAS 3006-64-2)	TWA	20 ppm		
US. NIOSH: Pocket Guide to Chemi	cal Hazards			
Components	Туре	Value	Form	
1,1,2-trichloroethylene (CAS 79-01-6)	TWA	25 ppm		
Butanone (CAS 78-93-3)	STEL	885 mg/m3 300 ppm		
	TWA	590 mg/m3 200 ppm		

Material name: LPS® HDX sps us

US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value	Form	
Camphor USP (CAS 76-22-2)	TWA	2 mg/m3		
Diphenyl Oxide (CAS 101-84-8)	TWA	7 mg/m3	Vapor.	
		1 ppm	Vapor.	
Iso amyl acetate (CAS 123-92-2)	TWA	525 mg/m3		
,		100 ppm		
Turpentine (CAS 8006-64-2)	TWA	560 mg/m3		
,		100 ppm		
US. Workplace Environmental Ex	posure Level (WEEL) Guides			
Components	Type	Value		
1,2 Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m3		
•		2 ppm		

Biological limit values

ACGIH	Biological	Exposure	Indices
AUGIII	Diological	Lxposure	IIIuices

Components	Value	Determinant	Specimen	Sampling Time
1,1,2-trichloroethylene (CAS 79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
	0.5 mg/l	Trichloroethano I, without hydrolysis	Blood	*
Butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protectionUse a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not

provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Light brown. Sweet, Spice. Odor Odor threshold Not established Not applicable Melting point/freezing point Not established 188.6 °F (87 °C) Initial boiling point and boiling range

 SDS US

4/10

Flash point Tag Closed Cup (None)
Evaporation rate 0.3 (Ethyl Ether = 1)
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

10.5 %

8 %

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 58 mm Hg @ 20°C

Vapor density 4.5

Relative density Not available.

Solubility(ies)

Solubility (water) 0.1 % Partition coefficient 2.4

(n-octanol/water)

Auto-ignition temperature> 788 °F (> 420 °C)Decomposition temperatureNot establishedViscosity0.53 cP @ 25° C

Other information

Explosive propertiesNot explosive.Heat of combustion< 20 kJ/g</th>Oxidizing propertiesNot oxidizing.

Percent volatile 100 %

Specific gravity 1.41 - 1.47 @ 20°C

VOC 97.8 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

toxicological characteristics cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects.

Material name: LPS® HDX

Components **Species Test Results**

1,1,2-trichloroethylene (CAS 79-01-6)

Acute Dermal

LD50 Rabbit 20 ml/kg

Inhalation

LC50 Rat 12500 ppm, 4 Hours

Oral

4920 mg/kg LD50 Rat

1,2 Butylene Oxide (CAS 106-88-7)

Acute Dermal

LD50 Rabbit 1.77 ml/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 6.3 mg/l, 4 Hours

Oral

LD50 Rat 1100 µl/kg

Butanone (CAS 78-93-3)

Acute Dermal

LD50 Rabbit > 10 ml/kg

Oral

LD50 Rat 2054 mg/kg

Diphenyl Oxide (CAS 101-84-8)

Acute Oral

LD50 Rat 2.83 g/kg

Turpentine (CAS 8006-64-2)

Acute **Dermal**

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat 13.7 mg/l, 4 Hours

Oral

LD50 Rat 4.6 ml/kg

Causes skin irritation. Skin corrosion/irritation Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

ACGIH sensitization

Turpentine (CAS 8006-64-2) Dermal sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Suspected of causing genetic defects. Germ cell mutagenicity

May cause cancer. Carcinogenicity

ACGIH Carcinogens

1,1,2-trichloroethylene (CAS 79-01-6) A2 Suspected human carcinogen.

Camphor USP (CAS 76-22-2) A4 Not classifiable as a human carcinogen. Turpentine (CAS 8006-64-2) A4 Not classifiable as a human carcinogen.

Material name: LPS® HDX SDS US 6/10

IARC Monographs. Overall Evaluation of Carcinogenicity

1,1,2-trichloroethylene (CAS 79-01-6)

1 Carcinogenic to humans.

1,2 Butylene Oxide (CAS 106-88-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

1,1,2-trichloroethylene (CAS 79-01-6) Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
1,1,2-trichloroethylene	e (CAS 79-01-6)		
Aquatic			
Fish	LC50	Flagfish (Jordanella floridae)	3.1 mg/l, 96 hours
Butanone (CAS 78-93	3-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
Diphenyl Oxide (CAS	101-84-8)		
Aquatic			
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	1.8 - 3.2 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

LPS® HDX 2.4 1,1,2-trichloroethylene 2.61 Butanone 0.29 Diphenyl Oxide 4.21

Mobility in soil No data available. Other adverse effects None known.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

D040: Waste Trichloroethylene

F001

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: LPS® HDX SDS US 7 / 10 01005, 01055 Version #: 01 Issue date: 10-18-2016

14. Transport information

DOT

UN1710 **UN number**

Trichloroethylene UN proper shipping name

Transport hazard class(es)

Class 6.1(PGIII)

Subsidiary risk Label(s) 6.1 Packing group Ш **Environmental hazards**

> Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, N36, T4, TP1

Packaging exceptions 153 Packaging non bulk 203 Packaging bulk 241

IATA

UN1710 **UN number**

UN proper shipping name Transport hazard class(es)

Trichloroethylene

6.1(PGIII) Class

Subsidiary risk Ш **Packing group Environmental hazards** No **ERG Code** 6A

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1710

UN proper shipping name TRICHLOROETHYLENE

Transport hazard class(es)

Class 6.1(PGIII)

Subsidiary risk **Packing group** Ш

Environmental hazards

Marine pollutant No F-A, S-A **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Material name: LPS® HDX SDS US 8 / 10



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

1,1,2-trichloroethylene (CAS 79-01-6) 0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,1,2-trichloroethylene (CAS 79-01-6) Listed. 1,2 Butylene Oxide (CAS 106-88-7) Listed. Butanone (CAS 78-93-3) Listed. Iso amyl acetate (CAS 123-92-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. **TRICHLOROETHYLENE** 79-01-6 99.85

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1.1.2-trichloroethylene (CAS 79-01-6)

1,2 Butylene Oxide (CAS 106-88-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

6714 Butanone (CAS 78-93-3)

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

35 %WV Butanone (CAS 78-93-3)

DEA Exempt Chemical Mixtures Code Number

Butanone (CAS 78-93-3) 6714

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Butanone (CAS 78-93-3) Low priority Diphenyl Oxide (CAS 101-84-8) Low priority Iso amyl acetate (CAS 123-92-2) Low priority

Material name: LPS® HDX SDS US 9/10 WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,1,2-trichloroethylene (CAS 79-01-6) Listed: April 1, 1988 US - California Proposition 65 - CRT: Listed date/Developmental toxin

1,1,2-trichloroethylene (CAS 79-01-6) Listed: Jan 31, 2014

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

1,1,2-trichloroethylene (CAS 79-01-6) Listed: Jan 31, 2014

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,1,2-trichloroethylene (CAS 79-01-6) 1,2 Butylene Oxide (CAS 106-88-7)

Butanone (CAS 78-93-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-18-2016

Version # 01

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use. processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

Material name: LPS® HDX 10 / 10

01005, 01055 Version #: 01 Issue date: 10-18-2016