

Wolf's Head Oil Company 1601 McCloskey Boulevard Tampa, FL 33605-6710 U.S.A. Telephone: (813) 248-1988 • Fax: (813) 241-1488 Email: <u>info@wolfshead.com</u> • www.wolfshead.com

MATERIAL SAFETY DATA SHEETS

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

GENERIC NAME: LUBRICATING MOTOR OIL

ISSUE DATE: MARCH 2008

THIS MSDS REPRESENTS THE FOLLOWING WOLF'S HEAD PRODUCTS:

SYN-PACK 100% SYNTHETIC 5W20, 5W30

CAS NUMBER: SYNONYMS / GENERAL NAMES: 24 HOUR EMERGENCY TELEPHONE: TECHNICAL INFORMATION: MIXTURE MOTOR OIL (CHEMTREC) 1-800-424-9300 1-800-368-1264 x185

2. COMPOSITION / INFORMATION ON INGREDIENTS / HAZARDOUS INGREDIENTS

	COMPONENTS/COMMON NAMES	CAS NO.	%	HAZARD DATA
1)	HIGHLY-REFINED SYNTHETIC BASE OILS	64742-54-7	0-85	ORAL (LD50): >5000 mg/kg
2)	PETROLEUM ADDITIVES	MIXTURE	10-25	DERMAL (LD50): >2000 mg/kg
3)	ZINC ALKYLDITHIOPHOSPHATE	68649-42-3	<1	

HAZARDOUS INGREDIENTS: NONE

HAZARDOUS PER 29 CFR 1916.1200: NO

3. HAZARDOUS IDENTIFICATION

ROUTES OF ENTRY:	SKIN CONTACT
TARGET ORGANS:	SKIN
IRRITANCY:	THIS PRODUCT CAN CAUSE MILD, TRANSIENT, EYE IRRITATION WITH SHORT-TERM CONTACT WITH LIQUID OR SPRAYS.
REPRODUCTIVE EFFECTS:	N/A
CANCER INFORMATION:	THIS PRODUCT DOES NOT CONTAIN ANY COMPONENTS AT CONCENTRATIONS ABOVE 0.1% WHICH ARE CONSIDERED CARCINOGENIC BY OSHA, IARC, OR NTP.

4. FIRST AID MEASURES

EYES:	CHECK FOR AND REMOVE CONTACT LENSES. FLUSH EYES WITH COOL, CLEAN, LOW-PRESSURE
	WATER WHILE OCCASIONALLY LIFTING AND LOWERING EYELIDS. SEEK MEDICAL ATTENTION IF
	EXCESSIVE TEARING, REDNESS, OR PAIN PERSISTS.
DERMAL:	REMOVE CONTAMINATED SHOES AND CLOTHING. WIPE OFF EXCESS MATERIAL. WASH EXPOSED SKIN
	WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF TISSUE APPEARS DAMAGED OR IF IRRITATION
	PERSISTS. THOROUGHLY CLEAN CONTAMINATED CLOTHING BEFORE REUSE. DISCARD
	CONTAMINATED LEATHER GOODS.
INGESTION:	DO NOT INDUCE VOMITING UNLESS DIRECTED TO BY A PHYSICIAN. DO NOT GIVE ANYTHING TO DRINK
	UNLESS DIRECTED TO BY A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO A PERSON WHO IS NOT
	FULLY CONSCIOUS. SEEK MEDICAL ATTENTION IMMEDIATELY.
INHALATION:	MOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, IMMEDIATELY BEGIN RESCUE BREATHING.
_	IF BREATHING IS DIFFICULT, 100 PERCENT HUMIDIFIED OXYGEN SHOULD BE ADMINISTERED BY A
	QUALIFIED INDIVIDUAL. SEEK MEDICAL ATTENTION IMMEDIATELY. KEEP THE AFFECTED INDIVIDUAL
	WARM AND AT REST.
INJECTION:	INJECTION OF PRESSURIZED HYDROCARBONS CAN CAUSE SEVERE, PERMANENT TISSUE DAMAGE.
	INITIAL SYMPTOMS MAY BE MINOR. INJECTION OF PETROLEUM HYDROCARBONS REQUIRES IMMEDIATE
	MEDICAL ATTENTION.

ND - NO DATA

NE - NOT ESTABLISHED

5. FIRE FIGHTING MEASURES

_		
	FLASH POINT, °C(°F):	222°C(431F)
	FLAMMABLE LIMITS (% BY VOLUME):	LOWER: NO DATA UPPER: NO DATA
	EXTINGUISHING MEDIA:	USE DRY CHEMICAL, FOAM, CARBON DIOXIDE OR WATER FOG.
	SPECIAL FIRE FIGHTING PROCEDURE	
	AUTOIGNITION TEMPERATURE:	N/A
	EXPLOSION DATA:	N/A
	NFPA RATING:	HEALTH: <u>1</u> FLAMMABILITY: <u>1</u> REACTIVITY <u>0</u>
_		
6	. ACCIDENTAL RELEASE MEASURES	
	APPROPRIA SPILLED MA ABSORB OR	UCH DAMAGED CONTAINERS OR SPILLED MATERIAL UNLESS WEARING TE PROTECTIVE EQUIPMENT. SLIPPING HAZARD; DO NOT WALK THROUGH TERIAL. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. FOR SMALL SPILLS, COVER WITH DRY EARTH, SAND, OR OTHER INERT NON-COMBUSTIBLE T MATERIAL AND PLACE INTO WASTE CONTAINERS FOR LATER DISPOSAL.
	CONTAIN LA INTO WATEI NATURAL EI PHYSICAL H AND SIMILA	ARGE SPILLS TO MAXIMIZE PRODUCT RECOVERY OR DISPOSAL. PREVENT ENTRY RWAYS OR SEWERS. IN URBAN AREA, CLEANUP SPILL AS SOON AS POSSIBLE. IN NVIRONMENTS, SEEK CLEANUP ADVICE FROM SPECIALISTS TO MINIMIZE HABITAT DAMAGE. THIS MATERIAL WILL FLOAT ON WATER. ABSORBENT PADS R MATERIALS CAN BE USED. COMPLY WITH ALL LAWS AND REGULATIONS.
7	. HANDLING AND STORAGE	
		ATER CONTAMINATION AND EXTREME TEMPERATURES TO MINIMIZE PRODUCT
	IGNITE WI DRILL, GR IGNITION BEFORE F CONTAINE STORAGE PROCEDURES: STORE AT PERIODS BEFORE F	ATTON: LIMIT TO CONTAINENTS MAT CONTAIN TROUDED THAT CAN THE EXPLOSIVE FORCE. DO NOT PRESSURIZE, CUT, WELD, BRAZE SOLDER, RIND OR EXPOSE CONTAINERS TO FLAMES, SPARKS, HEAT OR OTHER POTENTIAL SOURCES. CONSULT APPROPRIATE FEDERAL, STATE AND LOCAL AUTHORITIES REUSING, RECONDITIONING, RECLAIMING, RECYCLING OR DISPOSING OF EMPTY ERS AND/OR WASTE RESIDUES OF THIS PRODUCT. NTAINER CLOSED. DO NOT STORE WITH STRONG OXIDIZING AGENTS. DO NOT I TEMPERATURES ABOVE 120°F OR IN DIRECT SUNLIGHT FOR EXTENDED OF TIME. CONSULT APPROPRIATE FEDERAL, STATE AND LOCAL AUTHORITIES REUSING, RECONDITIONING, RECLAIMING, RECYCLING OR DISPOSING OF EMPTY ERS OR WASTE RESIDUES OF THIS PRODUCT.
8	. EXPOSURE CONTROLS / PERSONAL	PROTECTION
		PROVIDE EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP THE AIRBORNE CONCENTRATIONS OF MISTS AND/OR VAPORS BELOW THE RECOMMENDED EXPOSURE LIMITS. AN EYE WASH STATION AND SAFETY SHOWER SHOULD BE LOCATED NEAR THE WORK-STATION.
		USE GLOVES CONSTRUCTED OF CHEMICAL RESISTANT MATERIALS SUCH AS NEOPRENE OR HEAVY NITRILE RUBBER IF FREQUENT OR PROLONGED CONTACT IS EXPECTED. USE HEAT PROTECTIVE GLOVES WHEN HANDLING PRODUCT AT ELEVATED TEMPERATURES.
		SAFETY GLASSES EQUIPPED WITH SIDE SHIELDS SHOULD BE ADEQUATE PROTECTION UNDER MOST CONDITIONS OF USE. WEAR GOGGLES AND/OR FACE SHIELD IF SPLASHING OR SPRAYING IS LIKELY, ESPECIALLY IF MATERIAL IS HEATED ABOVE 125° F (OR 51° C). HAVE SUITABLE EYE WASH WATER AVAILABLE.
		VAPORIZATION OR MISTING IS NOT EXPECTED AT AMBIENT TEMPERATURES. THEREFORE, THE NEED FOR RESPIRATORY PROTECTION IS NOT ANTICIPATED UNDER NORMAL USE CONDITIONS AND WITH ADEQUATE VENTILATION. IF ELEVATED AIRBORNE CONCENTRATIONS ABOVE APPLICABLE WORKPLACE EXPOSURE LEVELS ARE ANTICIPATED, A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR EQUIPPED WITH A DUST/MIST PREFILTER SHOULD BE USED. PROTECTION FACTORS VARY DEPENDING UPON THE TYPE OF RESPIRATOR USED. RESPIRATORS SHOULD BE USED IN ACCORDANCE WITH OSHA

	REQUIREMENTS (29 CFR 1910.134).
CLOTHING RECOMMENDATION:	AVOID PROLONGED AND/OR REPEATED SKIN CONTACT, ESPECIALLY AFTER THIS
	PRODUCT HAS BEEN USED IN A CRANKCASE. IF SPLASHING OR SPRAYING IS
	EXPECTED, CHEMICAL-RESISTANT (TYVEK®, NITRILE, OR NEOPRENE)
	PROTECTIVE CLOTHING SHOULD BE WORN. THIS MIGHT INCLUDE LONG-
	SLEEVES, APRON, SLICKER SUIT, BOOTS, AND ADDITIONAL FACIAL PROTECTION.
	IF GENERAL CONTACT OCCURS, PROMPLY REMOVE SOAKED CLOTHING AND
	TAKE A SHOWER.

NA - NOT APPLICABLE

ND - NO DATA

NE - NOT ESTABLISHED

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

AMBER COLORED LIQUID

ODOR:	MILD PETROLEUM ODOR
pH:	N/A
VAPOR PRESSURE, mm Hg (25 °C):	<0.0001
VAPOR DENSITY:	10+ (AIR =1)
MELTING POINT:	NOT AVAILABLE.
BOILING POINT, 760 mm Hg, °C:	NOT AVAILABLE
SOLUBILITY IN WATER:	INSOLUBLE IN COLD WATER.
SPECIFIC GRAVITY:	0.86 (WATER = 1)
EVAPORATION RATE:	N/A
VISCOSITY 40°C (100°C)	N/A
MOLECULAR WEIGHT:	N/A
PERCENT VOLATILE:	NEGLIGIBLE VOLATILITY

10. STABILITY AND REACTIVITY

STABILITY:	STABLE
INCOMPATIBILITY:	STRONG OXIDIZERS
POLYMERIZATION:	NOT EXPECTED TO OCCUR
THERMAL DECOMPOSITION:	CO2, CO, SMOKE, FUMES, UNBURNED HYDROCARBONS AND TRACE OXIDES OF
	SULFUR, NITROGEN, PHOSPHORUS AND ZINC.

11. TOXICOLOGICAL INFORMATION

EYE IRRITATION:	THIS PRODUCT CAN CAUSE MILD, TRANSIENT, EYE IRRITATION WITH SHORT-
	TERM CONTACT WITH LIQUID OR SPRAYS.
DERMAL IRRITATION:	THIS MATERIAL CAN CAUSE MILD, TRANSIENT SKIN IRRITATION WITH SHORT-
	TERM EXPOSURE.
INHALATION TOXICITY:	NO SIGNIFICANT ADVERSE HEALTH EFFECTS ARE EXPECTED TO OCCUR UPON
	SHORT-TERM EXPOSURE TO THIS PRODUCT. ASPIRATION OF LIQUID INTO THE
	LUNGS CAN CAUSE SEVERE LUNG DAMAGE OR DEATH.
INGESTION IRRITATION:	IF SWALLOWED, NO SIGNIFICANT ADVERSE HEALTH EFFECTS ARE ANTICIPATED.
	INGESTION CAN CAUSE MILD IRRITATION TO THE DIGESTIVE TRACT OR CAUSE A
	LAXATIVE EFFECT.
INJECTION SENSITATION:	INJECTION UNDER THE SKIN, IN MUSCLE, OR INTO THE BLOOD STREAM CAN
	CAUSE IRRITATION, INFLAMMATION, SWELLING, FEVER, AND SYSTEMIC EFFECTS
	AND MILD CENTRAL NERVOUS SYSTEM DEPRESSION. INJECTION OF
	PRESSURIZED HYDROCARBONS CAN CAUSE SEVERE, PERMANENT TISSUE
	DAMAGE. INITIAL SYMPTOMS MAY BE MINOR. INJECTION OF PETROLEUM
	HYDROCARBONS REQUIRES IMMEDIATE MEDICAL ATTENTION.
CHRONIC EXPOSURE SYMPTOMS	PROLONGED OR REPEATED CONTACT CAN CAUSE MILD SKIN IRRITATION AND
	INFLAMMATION CHARACTERIZED BY DRYING, CRACKING, (DERMATITIS) OR OIL

12. HEALTH INFORMATION

HMIS CODE: HEALTH: <u>1</u> FIRE: <u>1</u> REACTIVITY: <u>0</u>

ACNE.

No	HIGHLY TOXIC	No	SENSITIZER
No	TOXIC	No	REPRODUCTIVE EFFECTS
No	CORROSIVE	No	MUTAGEN
No	IRRITANT		

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Determine compliance status with all applicable requirements prior to disposal.

NA - NOT APPLICABLE	ND - NO DATA	NE - NOT ESTABLISHED
14. TRANSPORT INFORMATION		

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME:	PETROLEUM LUBRICATING OIL
HAZARD CLASS:	NOT A DOT CONTROLLED MATERIAL (UNITED STATES).

HAZARD IDENTIFICATION NUMBER:	N/A
DOT PLACARD:	N/A
COMPATIBILITY CATEGORY:	N/A

15. REGULATORY INFORMATION

SARA SECTION 313 - TOXIC CHEMICALS:

This product does contain toxic chemicals under SARA Section 313 and 40 CFR Part 372.

COMPONENTS	<u>CAS #</u>	<u>%</u>
-------------------	--------------	----------

SARA SECTION 311 - HAZARD CATEGORIES:

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established be Sections 311 and 312 of SARA as indicated below:

NO	IMMEDIATE (ACUTE) HEALTH HAZARD	NO	SUDDEN RELEASE OF PRESSURE HAZARD
NO	DELAYED (CHRONIC) HEALTH HAZARD	NO	REACTIVE HAZARD
NO	FIRE HAZARD		

SARA SECTION 302 - EXTREMELY HAZARDOUS WASTE:

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

CLEAN WATER ACT (CWA):

Under the CWA, discharges of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

CERCLA HAZARDOUS SUBSTANCES:

As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as a hazardous substance.

U.S. TSCA INVENTORY

All components of this material are on the U.S. TSCA Inventory or are not required to be listed on the U.S. TSCA Inventory

16. OTHER INFORMATION

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT.WOLF'S HEAD BELIEVES THIS INFORMATION TO BE RELIABLE AND UP TO DATE AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.

NFPA HAZARD RATING	least - 0	slight - 1	moderate - 2	high - 3	extreme - 4
HMIS HEALTH RATING	least - 0	slight - 1	moderate - 2	high - 3	extreme - 4

NA - NOT APPLICABLE

ND - NO DATA

NE - NOT ESTABLISHED