Safety Data Sheet

Per GHS Standard Format

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: ProCoustic Acoustical Tile & Ceiling Coatings:

79400 White, 79494 Deep Base, 79495 Neutral Base,. Also ProCoat 79401 white, ProCoustic Black and

ProCoustic 79499 Special Colors.

Recommended Use of Product: Coating for interior acoustical substrates and ceilings.

Information on the Supplier of the Safety Data Sheet

Manufactured For:
ProCoat Products, Inc.

260 Centre Street, Suite D
Holbrook, MA 02343

Manufacturer's Information:
Emergency Telephone Numbers:
CHEM TEL: (US): 1-800-255-3924
(Outside the US): 813-248-0585

Information Phone: 781-767-2270

FAX: 781-767-2271

SECTION 2: HAZARDS IDENTIFICATION

Signal Word: WARNING





GHS Label Statements

Hazard Statements:
Harmful if inhaled
Causes serious eye irritation
Harmful if ingested
Suspected of causing cancer

Classification

SDS DATE: December, 2015

This product is considered hazardous by The 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Acute Toxicity-Inhalation (Dust-mists) Category 2 Serious eye damage/eye irritation – Category 2

PRECAUTIONARY STATEMENTS

Carcinogenicity - Category 2

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed, labeled and land-filled or incinerated according to local, regional and national regulations.

Hazards Not Otherwise Classified (NHOC): Not applicable.

Other Information: Toxic to aquatic life with long lasting effects. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight, %**
*Titanium dioxide	13463-67-7	1-4
Calcium carbonate	1317-65-3	10-30
Vinyl acrylic resin solids	Proprietary	2-4
Aluminum silicate	1332-58-7	2-4
Lithium silicate	12627-14-4	2-4

^{*}Not in No. 79495 Neutral Base

SECTION 4: FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. Remove and isolate contaminated clothing and shoes at site.

Eye Contact

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin Contact

Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.

Inhalation

Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately. If not breathing, give artificial respiration. Do not breathe dust.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid breathing vapors or mists

^{**} The exact concentration of composition has been withheld as a trade secret. Special non-hazardous tint colors added for black and custom colors

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Coughing and/or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. May cause sensitization of susceptible persons.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be insufficient.

Specific Hazards Arising from the Chemical

Product is/or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Sensitizer: Liquid Toxic: Liquid

Hazardous Combustion Products

Carbon oxides

Explosion Data

Sensitivity to Mechanical Impact NO.

Sensitivity to Static Impact NO.

Protective Equipment and Precautions for Fire Fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, OSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Avoid contact with skin, eyes, clothing. Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid generation of dust.

Other Information

Refer to protective measures listed in Sections 7 & 8.

Environmental Precautions

Environmental Precautions

Refer to protective measures listed in Sections 7 & 8

Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion. Of absorbent material contaminated with this product. Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Keep away from contact with clothing and other combustible materials to avoid fire.

Conditions for Safe Storage, Including any Incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of reach of children.

Incompatible Products

None known based on information supplied

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name Lithium silicate 12627-14-4	ACGIH TLV None established	OSHA PEL None Established	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/ m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Calcium carbonate 1317-65-3		TWA: 15 mg/ m ³ TWA: 5 mg/ m ³ (vacated) TWA: 15 mg/m ³ (vacated) TWA: 5 mg/m ³	TWA: 5 mg/ m ³ respirable dust TWA: 10 mg/ m ³ total dust
Aluminum silicate	TWA 2mg/m ³	10 mg/ m ³ (total dust)	No Data Available

ACGIH TLV: American Conference of Governmental Industrial Hygienists – Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration – Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate Engineering Controls

Engineering Measures

Showers / Eyewash Stations / Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection

If splashes are likely to occur, wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and body Protection

Wear protective gloves and protective clothing

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial and safety practices. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Viscous Liquid Odor: Very Slight

Appearance: Various Colors Odor Threshold: No Information Available

Color: No Information Available

Property ph	<u>Values</u> 8.5	Remarks/Method None Known
Melting/freezing point	No Data Available	None Known
Boiling Point	No Data Available	None Known
Flash Point	No Data Available	None Known
Evaporation rate	No Data Available	None Known
Flammability (solid, gas)	No Data Available	None Known
Flammability Limit in Air		
Upper flammability limit	No Data Available	None Known
Lower flammability limit	No Data Available	None Known
Vapor pressure	No Data Available	None Known
Vapor density	No Data Available	None Known
Specific Gravity	No Data Available	None Known
Water Solubility	Miscible in water	None Known
Solubility in other solvents	No Data Available	None Known
Partition coefficient: n-octanol/water	No Data Available	None Known
Auto ignition temperature	No Data Available	None Known
Decomposition temperature	No Data Available	None Known
Kinematic viscosity	No Data Available	None Known
Explosive properties	No Data Available	
Oxidizing properties	No Data Available	

Page 6 of 10 ProCoustic Acoustical Tile & Ceiling Coating ALL BASES SDS DATE: December, 2015

Other Information

Softening Point No Data Available.

VOC Content (%) > 1%

Particle Size No Data Available Particle Size Distribution No Data Available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Conditions to Avoid

No Data Available Excessive Heat

<u>Chemical Stability</u> <u>Incompatible Materials</u>

Stable under recommended storage conditions

None known based on information provided

<u>Possibility of Hazardous Reactions</u>
<u>Hazardous Decomposition Products</u>

None under normal processing Carbon oxides

Hazardous Polymerization

Hazardous polymerization does not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely Routes of Exposure

Product Information

Product does not present an acute toxicity hazard based on known or supplied information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation (based on components)

Eve Contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching and pain. May cause temporary eye irritation.

Skin Contact

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rat)		
13463-67-7 Aluminum silicate 57-55-6	>5000 mg/kg (Rat)	>5000 mg/kg (Rabbit)	(Dust) 6.9 mg/L (Rat) 4 hr.

Page 7 of 10 ProCoustic Acoustical Tile & Ceiling Coating ALL BASES SDS DATE: December, 2015

Chemical Name
Lithium silicate

12627-14-4

Oral LD50
Oral LD50 >2000
mg/kg (Rat) (OECD 423)

Dermal LD50
Irritation to skin
IS 111.5% (in-vitro)
EpiDerm-Test
Irritation of eyes
IS 3 (Rabbit) (OECD 405)

Inhalation LC50 cont...
No Data Available

Information on Toxicological Effects

Symptoms

May cause redness and tearing of the eyes, coughing and/or wheezing, itching, rashes and hives.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Sensitization

May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects

No Information Available

Carcinogenicity

The table below indicates whether each agency has listed any ingredients as a carcinogen

Chemical NameACGIHIARCNTPOSHATitanium dioxideGroup 2BX13463-67-7

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 – Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B – Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X-Present

Reproductive Toxicity, STOT Single Exposure, STOT Repeated Exposure:

No Information Available

Chronic Toxicity

Titanium Dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. Contains a known or suspected carcinogen.

Target Organ Effects

Eyes, respiratory system, skin, gastrointestinal tract (GI) & lungs.

Aspiration Hazard

No Information Available

Numerical Measures of Toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (Inhalation-dust/mist) ATEmix (Oral)

8,711.00 mg/kg 2.41 mg/l

ATEmix (Dermal) ATEmix (Inhalation-vapor)

21,608.00 mg/kg (ATE) 16.00 ATEmix

ATEmix (Inhalation-gas)

3,118.00 ppm (4hr)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

Chemical Name Toxicity to Algae Toxicity to Fish Toxicity to Daphnia Magna

Microorganisms

Aluminum silicate LC5072h 71000mg/L LC5096h LC50>1000 mg/L No Data Available EC50: 48h 71000 mg/L

Lithium silicate

Do not allow product to reach sewage system, groundwater and any water course

12627-14-4

Persistence and Degradability

No Information Available

Bioaccumulation

No Information Available

Other Adverse Effects

No Information Available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal Regulations (40 CFR 261). This material could become a hazardous waste if it is mixed or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is process or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes

331

Page 9 of 10

SECTION 14: TRANSPORT INFORMATION

DOTProper Shipping Name

Not Regulated
Not Regulated

Hazard Class N/A

TDG

No Data Available

<u>IATA</u>

No Data Available

IMDG/IMO

No Data Available

SECTION 15: REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** – Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

No Data Available

SARA 311/312 Hazard Categories

Acute Health Hazard YES
Chronic Health Hazard YES
Fire Hazard NO
Sudden release of pressure hazard NO
Reactive Hazard NO

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) 40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemical

Chemical Name

California Proposition 65

Titanium dioxide – 13463-67-7

Carcinogen

U.S. State Right-to-know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Titanium dioxide -13463-67-4	X	Χ	X		
Calcium carbonate – 1317-65-3	X	Χ	X		
Aluminum silicate – 1332-58-7	X	Χ	X		
Lithium silicate – 12627-14-4	X	X	Χ		

International Regulations

Canada
WHMIS Hazard Class
D2A - Very Toxic Materials
D2B – Toxic Materials



SECTION 16: OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 0	Instability 0	Physical and Chemical Hazards Personal Protection
HMIS	Health Hazards 2*	Flammability 0	Physical Hazard 0	X

Chronic Hazard Star Legend * = Chronic Health Hazard

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD (5323) or log on to: www.epa.gov/lead