

## SAFETY DATA SHEET

Revision Date 03-Mar-2016 Version 3

## 1. IDENTIFICATION

Product identifier

Product Name THE RIGHT STUFF GASKET MAKER 7 OZ AE

Other means of identification

Product Code 25224 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
6875 Parkland Blvd. 35 Brownridge Road, Unit 1
Solon, OH 44139 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

## 2. HAZARDS IDENTIFICATION

#### Classification

## **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Gases under pressure	Compressed gas

#### Label elements

#### **Emergency Overview**

## Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer

Contains gas under pressure; may explode if heated



Appearance Black Physical state Paste Odor Mild

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

#### **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Store in a well-ventilated place

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

## Other Information

- Harmful to aquatic life with long lasting effects

Unknown acute toxicity

10.294 % of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

## substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
CALCIUM CARBONATE	471-34-1	15 - 40	*
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	15 - 40	*
POLYDIMETHYLSILOXANE	63148-62-9	7 - 13	*
VINYL OXIMINOSILANE	2224-33-1	1 - 5	*
NITROGEN	7727-37-9	1 - 5	*
STEARIC ACID	57-11-4	1 - 5	*
CARBON BLACK	1333-86-4	1 - 5	*
2-BUTANONE OXIME	96-29-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

**Eve contact** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Contains gas under pressure; may explode if heated.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Remove all sources of ignition. Do not puncture or incinerate cans.

**Environmental precautions** 

Environmental precautions Do not flush into surface water or sanitary sewer system. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

AΕ

#### Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Methods for containment

Methods for cleaning up Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with Advice on safe handling

> skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Protect from

moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
CALCIUM CARBONATE 471-34-1	•	-	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust	
CARBON BLACK 1333-86-4	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic bydrocarbons PAH	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** Showers

> Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of **General Hygiene Considerations** 

equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Paste
Appearance Black
Odor Mild

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** 7-8

Melting point / freezing point No information available

Boiling point / boiling rangeNot ApplicablePolymerizationFlash point> 93 °C / > 200 °FTag Closed CupEvaporation rate< 1</td>Butyl acetate = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure

No information available
No information available
<5 mmHq @ 70°F

Vapor density 3 Air = 1

Relative density 1.34

Water solubility Not applicable

Solubility in other solvents No information available No information available **Partition coefficient Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available **Dynamic viscosity** No information available **Explosive properties Oxidizing properties** No information available

**Other Information** 

Softening point No information available Molecular weight No information available

VOC Content (%) <3%

DensityNo information availableBulk densityNo information available

## 10. STABILITY AND REACTIVITY

Polymerization

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

Risk of explosion if heated under confinement.

#### Conditions to avoid

Heat, flames and sparks.

#### Incompatible materials

Strong oxidizing agents, Acids, Water

#### **Hazardous Decomposition Products**

Carbon oxides

Nitrogen oxides (NOx)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	-	-
471-34-1			
POLY (DIMETHYLSILOXANE),	-	> 16 mL/kg (Rabbit)	> 8750 mg/m³ (Rat) 7 h
HYDROXY TERMINATED			
70131-67-8			
POLYDIMETHYLSILOXANE	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	-
63148-62-9			
STEARIC ACID	-	> 5 g/kg (Rabbit)	-
57-11-4			
CARBON BLACK	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			
2-BUTANONE OXIME	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
96-29-7			. , ,

## Information on toxicological effects

**Symptoms** No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation Causes serious eye irritation.

**Sensitization** May cause sensitization by skin contact.

**Germ cell mutagenicity** No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Lymphatic System, Respiratory system, Skin.

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10960 mg/kg ATEmix (dermal) 8999 mg/kg

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Nam	e A	Algae/aquatic plants	Fish	Crustacea
CARBON BLAC	K	-	-	5600: 24 h Daphnia magna mg/L
1333-86-4				EC50
2-BUTANONE OX	IME 83: 72 h	Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7		mg/L EC50	promelas mg/L LC50 flow-through	EC50

# 25224 - THE RIGHT STUFF GASKET MAKER 7 OZ AE

760: 96 h Poecilia reticulata mg/L	
LC50 static 320 - 1000: 96 h	
Leuciscus idus mg/L LC50 static	

## Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient	
2-BUTANONE OXIME	0.65	
96-29-7		

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

## 14. TRANSPORT INFORMATION

DOT

**UN/ID no** UN 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 Emergency Response Guide 126

Number

**IATA** 

**UN/ID no** ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID no UN 1950

**Proper shipping name:** Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 EmS-No F-D, S-U

## 15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

## 25224 - THE RIGHT STUFF GASKET MAKER 7 OZ AE

EINECS/ELINCS Not Listed.
ENCS Not Listed.
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
CARBON BLACK - 1333-86-4	Carcinogen

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
NITROGEN	X	X	X
7727-37-9			
CARBON BLACK	X	X	X
1333-86-4			
ALUMINIUM POWDER	X	X	X
7429-90-5			

## **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

## **WHMIS Hazard Class**

A Compressed gases, D2B - Toxic materials

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 03-Mar-2016

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**