

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Waterproof, polyethylene film with a carrier of polyester/cotton blend cloth
Adhesive: Natural rubber

PHYSICAL CHARACTERISTICS

STANDARD

METRIC

	Silver	Colors		Silver	Colors	
Tensile Strength	22	22	lbs./in. width	37.92	37.92	N/10mm
Adhesion to Stainless Steel	55	45	oz./in. width	5.92	4.31	N/10mm
Thickness	9.0	9.0	mils	.228	.228	mm
Elongation	15	10	%	15	10	%
Maximum Temperature	200°	200°	F	93°	93°	C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, Inc. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

COLOR(S)

Beige (BEI) Brown (BRN) Green (GRN) Purple (PRP) White (WHI)
Black (BLK) Burgundy (BRG) Olive Drab (OLV) Red (RED) Yellow (YEL)
Blue (BLU) Floral Green (FGN) Orange (ORG) Silver (SIL)

APPLICATIONS

- General purpose use in industrial, carpet, motorsports, plumbing, HVAC and asbestos abatement applications
- Waterproof packaging, bundling, patching, sealing and wrapping
- Color coding
- Holding, splicing, seaming and general repairs

PRODUCT BENEFITS

- Waterproof backing
- Good conformability on irregular surfaces
- Excellent adhesion
- Tears easily
- Competitively priced
- Good handling characteristics - does not twist or curl during application
- Versatile

APPLICABLE SPECIFICATIONS

Meets requirements of UL 723
Flame Spread Index 5
Smoke Development Index 20

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

ISO 9000 CERTIFIED QUALITY SYSTEM

Shurtape Technologies, Inc.

1506 Highland Avenue NE, Hickory, NC 28601 • PO Box 1530, Hickory, NC 28603-1530

Phone 828/322-2700 or 888/442-TAPE • Fax 828/322-4419 • Customer Service Fax 828/322-4029 or 800/335-7651