Safety Data Sheet



Section 1: Identification

Product Identifier · Conventional Gasoline

Synonyms

 Conventional Midgrade Unleaded Gasoline; Conventional Premium Unleaded Gasoline; Conventional Regular Unleaded Gasoline; Midgrade Unleaded Gasoline; Premium Unleaded Gasoline; Recreational Gasoline; Regular Unleaded Gasoline

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Fuel

Restrictions on use • All others

Details of the supplier of the safety data sheet

Manufacturer	 Guttman Energy, Inc.
	200 Speers Street
	Belle Vernon, PA 15012
	United States
	www.guttmanenergyfuels.com
	safety@guttmangroup.com

Emergency telephone number

Manufacturer

• 1-800-535-5053 - INFOTRAC

Section 2: Hazard Identification

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

Flammable Liquids 1
 Acute Toxicity Oral 4
 Aspiration 1
 Skin Irritation 2
 Eye Irritation 2
 Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
 Germ Cell Mutagenicity 1B
 Carcinogenicity 1A
 Reproductive Toxicity 1B
 Specific Target Organ Toxicity Repeated Exposure 1
 Specific Target Organ Toxicity Repeated Exposure 2

Label elements OSHA HCS 2012

DANGER

Preparation Date: 06/November/2015 Revision Date: 23/November/2015




Hazard statements	 Extremely flammable liquid and vapor Harmful if swallowed May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces No smoking. Keep container tightly closed. Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mists, vapors, and/or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	 In case of fire: Use appropriate media for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If on skin: Wash with plenty of water . Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention.
Storage/Disposal	 Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Other information



Section 3 - Composition/Information on Ingredients

Substances

• Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Benzine (motor fuel)	CAS: 86290- 81-5	0% TO 100%	NDA	OSHA HCS 2012: Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2; Muta. 1B; Repr. 1B; STOT SE 3: Narc. & Resp. Irrit.; STOT RE 1 (CNS, Blood, Bone Marrow, Eyes); Carc. 1A; STOT RE 2 (Ear, Nercous System); Acute Tox. 4 (Orl); Acute Tox. 4 (Inhl)	NDA
Toluene	CAS: 108- 88-3	0% TO 26%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Orl); Skin Irrit. 2; Eye Irrit. 2; Muta. 1B; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (CNS, Inhl); Asp. Tox. 1	NDA
Xylene	CAS: 1330-20-7	0% TO 22%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (InhI); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (InhI); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.	NDA
Cyclohexane	CAS: 110- 82-7	0% TO 7%	Ingestion/Oral-Rat LD50 • 6240 mg/kg Skin-Rabbit LD50 • >2000 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2; STOT SE 3: Narc.; Skin Irrit. 2; Asp. Tox. 1	NDA
Benzene	CAS: 71-43- 2	0% TO 5%	Ingestion/Oral-Rat LD50 • 930 mg/kg Skin-Rabbit LD50 • >9400 μL/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Orl); Acute Tox. 4 (Inhl); Skin Irrit. 2; Eye Irrit. 2; Muta. 1B (Orl, Inhl); Carc. 1A (Inhl); Repr. 2 (Inhl); STOT SE 3: Narc. (Inhl); STOT RE 1 (Blood, Bone marrow / Inhl); Asp. Tox. 1	NDA
1,2,4- Trimethylbenzene	CAS: 95-63- 6	0% TO 5%	Ingestion/Oral-Rat LD50 • 5 g/kg Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3: Resp. Irrit.; STOT SE 3: Narc.; Asp. Tox. 1;	NDA

Naphthalene	CAS: 91-20- 3	0% TO 4%	Skin-Rabbit LD50 • >20 g/kg Ingestion/Oral-Rat LD50 • 490 mg/kg	OSHA HCS 2012: Flam. Sol. 2; Acute Tox. 4 (Orl); Skin Irrit. 2; Muta. 2; Carc. 2; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (Blood, Eyes; Orl, Inhl)	NDA
Ethylbenzene	CAS: 100- 41-4	0% TO 4%	Ingestion/Oral-Rat LD50 • 3500 mg/kg Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s) Skin-Rabbit LD50 • >5000 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Inhl); Eye Irrit. 2; Carc. 2 (Inhl); Repr. 2 (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (Inhl); STOT RE 2 (Ear / Inhl); Asp. Tox. 1	NDA
Hexane	CAS: 110- 54-3	0% TO 3%	Ingestion/Oral-Rat LD50 • 25 g/kg Inhalation-Rat LC50 • 48000 ppm 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 2; Repr. 2; STOT RE 2 (CNS & Nervous System); Skin Irrit. 2; Eye Irrit. 2; STOT SE 3: Narc. & Resp. Irrit.; Asp. Tox. 1	NDA
1- Methylethylbenzene	CAS: 98-82- 8	0% TO 1%	Ingestion/Oral-Rat LD50 • 1400 mg/kg Skin-Rabbit LD50 • 12300 µL/kg Inhalation-Rat LC50 • 39000 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 3; Asp. Tox. 1; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3: Narc.; Carc. 2; Acute Tox. 4 (Orl); STOT SE 3: Resp. Irrit.;	NDA

Section 4: First Aid Measures

Description of first aid measures

Inhalation • Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.

- Skin
 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
- **Eye** In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Rinse mouth. Do NOT induce vomiting. Obtain medical attention immediately if ingested.

Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to
 Physician
 All treatments should be based on observed signs and symptoms of distress in the patient.
 Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire Fighting Measures

Extinguishing media

Suitable Extinguishing	• CAUTION: For mixtures containing a high percentage of an alcohol or polar solvent,
Media	alcohol-resistant foam may be more effective.
	SMALL FIRES: Dry chemical, CO2, water spray or alcohol-resistant foam.
	LARGE FIRES: Water spray, fog or alcohol-resistant foam.

Extinguishing Media

Unsuitable

•	Avoid	using	direct	water	stream

Special hazards arising from the substance or mixture

	5
Unusual Fire and	 HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
Explosion Hazards	Containers may explode when heated.
	Many liquids are lighter than water.
	Vapors may form explosive mixtures with air.
	Most vapors are heavier than air. They will spread along ground and collect in low or
	confined areas (sewers, basements, tanks).
	Vapors may travel to source of ignition and flash back.
	Vapor explosion hazard indoors, outdoors or in sewers.
	Runoff to sewer may create fire or explosion hazard.
Hazardous Combustion Products	No data available

Advice for firefighters

 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible. Move containers from fire area if you can do it without risk.
 LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions • CAUTION: Victim may be a source of contamination. Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE)

Emergency
 As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

• Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up
Stop leak if you can do it without risk.
Absorb or cover with dry earth, sand or other non-combustible material and transfer to
containers.
Use clean non-sparking tools to collect absorbed material.
A vapor suppressing foam may be used to reduce vapors.
All equipment used when handling the product must be grounded.
LARGE SPILLS: Dike far ahead of spill for later disposal.
LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed
spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling • Keep away from heat, sparks, and flame. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Do not breathe mist, vapors and/or spray. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective equipment, avoid direct contact. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage • Store in a tightly closed container. Store in a cool/low-temperature, well-ventilated place.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Exposure Limits/Guidelines					
	Result	ACGIH	NIOSH	OSHA		
- .	Ceilings	Not established	Not established	300 ppm Ceiling		
Toluene (108-88-3)	TWAs	20 ppm TWA	100 ppm TWA; 375 mg/m3 TWA	200 ppm TWA		
(100 00 0)	STELs	Not established	150 ppm STEL; 560 mg/m3 STEL	Not established		
	Ceilings	Not established	Not established	25 ppm Ceiling		
Benzene	STELs	2.5 ppm STEL	1 ppm STEL	5 ppm STEL (see 29 CFR 1910.1028)		
(71-43-2)	TWAs	0.5 ppm TWA	0.1 ppm TWA	10 ppm TWA (applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028); 1 ppm TWA		
Naphthalene	TWAs	10 ppm TWA	10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA; 50 mg/m3 TWA		
(91-20-3)	STELs	Not established	15 ppm STEL; 75 mg/m3 STEL	Not established		
1- Methylethylbenzene (98-82-8)	TWAs	50 ppm TWA	50 ppm TWA; 245 mg/m3 TWA	50 ppm TWA; 245 mg/m3 TWA		
Cyclohexane (110-82-7)	TWAs	100 ppm TWA	300 ppm TWA; 1050 mg/m3 TWA	300 ppm TWA; 1050 mg/m3 TWA		
Ethylbenzene	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA		
(100-41-4)	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established		
Xylene	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA		
(1330-20-7)	STELs	150 ppm STEL	Not established	Not established		
Hexane (110-54-3)	TWAs	50 ppm TWA	50 ppm TWA; 180 mg/m3 TWA	500 ppm TWA; 1800 mg/m3 TWA		
Benzine (motor	STELs	500 ppm STEL	Not established	Not established		
fuel) (86290-81-5)	TWAs	300 ppm TWA	Not established	Not established		
1,2,4- Trimethylbenzene (95-63-6)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established		

Exposure controls

Engineering • (Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

• Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure

	supplied air respirators should be worn for exposures to any components exceeding the established exposure limits.
Eye/Face	Wear safety goggles.
Skin/Body	 Wear appropriate gloves. Use nitrile rubber, viton or PVA gloves for repeated or prolonged skin exposure. Wear long sleeves and/or protective coveralls.
General Industrial Hygiene Considerations	 Always handle products in accordance with best industrial hygiene and safety practices in mind, specifically avoiding contact with skin, eyes and clothing.
Environmental Exposure Controls	 Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.
Key to abbreviations	

limits are exceeded or symptoms are experienced. Organic vapor chemical cartridge or

ACGIH = American Conference of Governmental Industrial Hygiene NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description

Physical Form	Liquid	Appearance/Description	Clear or colored liquid with strong hydrocarbon odor.
Color	Clear or colored.	Odor	Strong hydrocarbon odor.
Odor Threshold	No data available		
General Properties			
Boiling Point	70 to 437 F(21.1111 to 225 C)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	< 0.8 Water=1	Water Solubility	Slightly Soluble 0 to 1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	> 1 Air=1
Evaporation Rate	No data available	VOC (Wt.)	100 %
VOC (Vol.)	100 %	Volatiles (Wt.)	100 %
Volatiles (Vol.)	100 %		
Flammability			
Flash Point	-50 F(-45.5556 C) PMCC (Pensky-Martins Closed Cup)	UEL	7.6 %
LEL	1.4 %	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

• No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

• Hazardous polymerization not indicated.

Conditions to avoid

• Keep away from heat, sparks, and flame.

Incompatible materials

• No data available

Hazardous decomposition products

• No data available

Section 11 - Toxicological Information

Information on toxicological effects

Components				
Benzine (motor fuel) (0% TO 100%)	86290- 81-5	Acute Toxicity: Ingestion/Oral-Rat LD50 • 13.6 g/kg; <i>Behavioral</i> :Headache; <i>Lungs, Thorax, or</i> <i>Respiration</i> :Cough; <i>Sense Organs and Special Senses:Eye</i> :Conjunctive irritation; Mutagen: Unscheduled DNA synthesis • Ingestion/Oral-Mammal • 100 mg/kg; Sperm Morphology • Inhalation-Rat • 300 mg/m ³ 10 Week(s)-Intermittent; Reproductive: Inhalation-Rat TCLo • 300 mg/m ³ (1-19D preg); <i>Reproductive Effects:Specific</i> <i>Developmental Abnormalities</i> :Musculoskeletal system; <i>Reproductive Effects:Effects on</i> <i>Newborn</i> :Behavioral; <i>Reproductive Effects:Effects on Newborn</i> :Physical		
Toluene (0% TO 26%)	108-88- 3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s); Inhalation- Human TCLo • 200 ppm; <i>Brain and Coverings</i> : Recordings from specific areas of CNS; <i>Behavioral</i> : Antipsychotic; <i>Blood</i> : Changes in bone marrow not included above; Inhalation-Human TCLo • 1500 mg/m ³ 8 Hour(s); <i>Sense Organs and Special Senses:Eye</i> :Lacrimation; <i>Sense Organs and Special Senses:Eye</i> : Conjunctive irritation; <i>Behavioral</i> : Ataxia; Inhalation-Man TCLo • 50 ppm; <i>Kidney, Ureter, and Bladder</i> : Other changes in urine composition; Skin-Rabbit LD50 • 14100 µL/kg; Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Mouse TCLo • 250 ppm 4 Day(s)-Continuous; <i>Behavioral</i> : Convulsions or effect on seizure threshold; <i>Behavioral</i> : Abuse; Inhalation-Mouse TCLo • 50 ppm 12 Week(s)-Intermittent; <i>Brain and Coverings</i> : Other degenerative changes; Inhalation-Rat TCLo • 10 ppm 6 Hour(s) 13 Week(s)- Intermittent; <i>Brain and Coverings</i> : Other degenerative changes; <i>Biochemical</i> : Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects; Mutagen: Micronucleus test • Ingestion/Oral-Mouse • 200 mg/kg; Sister chromatid exchange • Inhalation- Human • 252 µg/L 19 Year(s); Cytogenetic analysis • Inhalation-Rat • 5400 µg/m ³ 16 Week(s)-Intermittent; Reproductive: Inhalation-Mouse TCLo • 500 mg/m ³ 24 Hour(s)(6-13D preg); <i>Reproductive Effects:Effects</i> on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Inhalation-Mouse TCLo • 200 ppm 7 Hour(s)(7-16D preg); <i>Reproductive Effects:Specific Developmental Abnormalities</i> :Urogenital system		
1,2,4- Trimethylbenzene (0% TO 5%)	95-63- 6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 5 g/kg; Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour(s); Mutagen: Sister chromatid exchange • Intraperitoneal-Mouse • 900 mg/kg		
Xylene (0% TO 22%)	1330- 20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; <i>Liver</i> :Other changes; <i>Kidney, Ureter, and</i> <i>Bladder</i> :Other changes; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Man LCLo • 10000 ppm 6 Hour(s); <i>Behavioral</i> :General anesthetic; <i>Lungs, Thorax, or Respiration</i> :Cyanosis; <i>Blood</i> :Other changes; Inhalation-Human TCLo • 200 ppm; <i>Sense Organs and Special Senses</i> :Olfaction:Other changes; <i>Sense Organs and Special Senses:Eye</i> :Conjunctive irritation; <i>Lungs, Thorax, or Respiration</i> :Other changes; Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Mouse TCLo • 1 g/m ³ 12 Hour(s)(6-15D preg); <i>Reproductive Effects:Effects on</i> <i>Embryo or Fetus</i> :Fetotoxicity (except death, e.g., stunted fetus); <i>Reproductive Effects:Specific</i> <i>Developmental Abnormalities</i> :Musculoskeletal system; Inhalation-Rat TCLo • 50 mg/m ³ 6 Hour(s)(1-21D preg); <i>Reproductive Effects:Effects on Fertility</i> :Post-implantation mortality; <i>Reproductive Effects:Effects</i> <i>on Embryo or Fetus</i> :Fetotoxicity (except death, e.g., stunted fetus); <i>Reproductive Effects:Effects</i> <i>on Embryo or Fetus</i> :Fetotoxicity (except death, e.g., stunted fetus); <i>Reproductive Effects:Effects</i> : <i>Effects</i> <i>on Embryo or Fetus</i> :Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Effects: <i>Effects</i> <i>Developmental Abnormalities</i> :Craniofacial (including nose and tongue)		
Benzene (0% TO 5%)	71-43- 2	Acute Toxicity: Ingestion/Oral-Rat LD50 • 930 mg/kg; <i>Behavioral</i> : Tremor ; <i>Behavioral</i> : Convulsions or effect on seizure threshold; Ingestion/Oral-Man LDLo • 50 mg/kg; Inhalation-Rat LC50 • 10000 ppm 7 Hour(s); Inhalation-Rat TCLo • 1 ppm 6 Hour(s); <i>Kidney, Ureter, and Bladder</i> : Other changes in urine composition; Skin-Rabbit LD50 • >9400 µL/kg;		

		Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate
		irritation; Multi-dose Toxicity: Inhalation-Mouse TCLo • 100 ppm 2 Week(s)-Intermittent; <i>Endocrine</i> :Differential effect of sex or castration on observed toxicity; <i>Blood</i> :Leukopenia; <i>Blood</i> :Changes in bone marrow not included above; Inhalation-Mouse TDLo • 100 ppm 6 Hour(s) 10 Day(s)-Intermittent; <i>Blood</i> :Changes in other cell count (unspecified); <i>Blood</i> :Changes in leucocyte (WBC) count; <i>Blood</i> :Changes in erythrocyte (RBC) count;
		Mutagen: Dominant lethal test • Ingestion/Oral-Mouse • 1 mg/kg; Cytogenetic analysis • Inhalation-Human • 125 ppm 1 Year(s); Cytogenetic analysis • Inhalation-Human • 0.1 ppm; Sister chromatid exchange • Inhalation-Mouse • 10 ppm 6 Hour(s); Micronucleus test • Inhalation-Rat • 1 ppm 6 Hour(s); Reproductive: Inhalation-Mouse TCLo • 20 ppm 6 Hour(s)(6-15D preg); Reproductive Effects:Specific Developmental Abnormalities:Blood and lymphatic system; Inhalation-Mouse TCLo • 5 ppm (6-15D preg); Reproductive Effects:Specific Developmental Abnormalities:Blood and lymphatic system; Inhalation-Rat TCLo • 570 mg/m ³ 24 Hour(s)(15D pre/1-22D preg); Reproductive Effects:Effects on Ferroductive Effects:Effects on Ferroductive Effects:Effects on Seven and lymphatic system; Inhalation-Rat TCLo • 670 mg/m ³ 24 Hour(s)(15D pre/1-22D preg); Reproductive Effects:Effects on Ferroductive Effects: Parenteral-Mouse TDLo • 4 g/kg (12D preg); Reproductive Effects:Effects on Newborn:Weaning or lactation index; Tumorigenic:Carcinogenic by RTECS criteria; Endocrine:Tumors; Blood:Leukemia; Inhalation-Human • 150 ppm 15 Minute(s) 8 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Blood:Leukemia
Ethylbenzene (0% TO 4%)	100-41- 4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3500 mg/kg; Inhalation-Guinea Pig LCLo • 2500 ppm 8 Hour(s); Behavioral:Coma; Inhalation-Mouse TCLo • 600 ppm 6 Minute(s); Lungs, Thorax, or Respiration:Respiratory depression; Skin-Rabbit LD50 • 17800 µL/kg; Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 15 mg 24 Hour(s)-Open • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 550 ppm 8 Hour(s) 5 Day(s)-Intermittent; Sense Organs and Special Senses:Ear:Change in acuity; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function; Inhalation-Rat TDLo • 200 ppm 13 Week(s)-Intermittent; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function; Mutagen: Specific locus test • Intraperitoneal-Mouse • 754 µmol/L; Micronucleus test • Unreported Route- Hamster • Embryo (Somatic cell) • 25 mg/L; Sister chromatid exchange • Unreported Route-Human • Lymphocyte (Somatic cell) • 10 mmol/L; Mutation in Mammalian Somatic Cells • Unreported Route-Mouse • Lymphocyte (Somatic cell) • 10 mmol/L; Mutation in Mammalian Somatic Cells • Unreported Route-Mouse • Lymphocyte (Somatic cell) • 80 mg/L; Reproductive: Inhalation-Rat TCLo • 1 g/m³ 24 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 1000 ppm (6-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 1000 ppm (6-20D preg); Reproductive Effects:Effects on Fertility:Busculoskeletal system; Inhalation-Rat TCLo • 600 mg/m³ 24 Hour(s)(7-15D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetal death; Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Inhalation-Rat TCLo • 96 ppm 7 Hour(s)(1-19D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Tumorigen / Carcinogenic Inhalation-Mouse TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs,
Naphthalene (0% TO 4%)	91-20- 3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDL0 • 158 mg/kg; Brain and Coverings:Other degenerative changes; Liver.Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport; Inhalation-Human TCL0 • 250 mg/m ³ ; Sense Organs and Special Senses:Eye:Lacrimation; Behavioral:Headache; Skin-Rabbit LD50 • >20 g/kg; Unreported-Guinea Pig LD50 • 1200 mg/kg; Behavioral:Somnolence (general depressed activity); Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDL0 • 4500 mg/kg 10 Day(s)-Intermittent; Brain and Coverings:Other degenerative changes; Ingestion/Oral-Rat TDL0 • 500 mg/kg 10 Day(s)-Intermittent; Behavioral:Sleep; Lungs, Thorax, or Respiration:Dyspnea; Mutagen: Specific locus test • Inhalation-Rat • 30 ppm 13 Week(s)-Intermittent; Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L; Reproductive: Ingestion/Oral-Rat TDL0 • 4500 mg/kg (7-14D preg); Reproductive Effects:Effects on Newborn:Live birth index; Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive); Ingestion/Oral-Rat TDL0 • 4500 mg/kg (6-15D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities; Tumorigen / Carcinogen: Inhalation-Mouse TCL0 • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Inhalation-Rat TCL0 • 60 ppm 6 Hour(s) 105 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors; Inhalation-Rat TCL0 • 1575 mg/kg 105 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors

Hexane (0% TO 3%)	110-54-	Acute Toxicity: Ingestion/Oral-Rat LD50 • 25 g/kg; Inhalation-Rat LC50 • 48000 ppm 4 Hour(s); Irritation: Eye-Rabbit • 10 mg • Mild irritation; Reproductive: Inhalation-Rat TCLo • 5000 ppm (6-19D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Specific Developmental Abnormalities:Urogenital system
Cyclohexane (0% TO 7%)	110-82- 7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 6240 mg/kg; <i>Behavioral</i> :Somnolence (general depressed activity); <i>Gastrointestinal</i> :Changes in structure or function of salivary glands; <i>Gastrointestinal</i> :Hypermotility, diarrhea; Irritation: Skin-Rabbit • 1548 mg 2 Day(s)-Intermittent; Multi-dose Toxicity: Inhalation-Mouse TCLo • 2000 ppm 90 Day(s)-Intermittent; <i>Behavioral</i> :Somnolence (general depressed activity); <i>Behavioral</i> :Changes in motor activity (specific assay)
1-Methylethylbenzene (0% TO 1%)	98-82- 8	Acute Toxicity: Ingestion/Oral-Rat LD50 • 1400 mg/kg; <i>Gastrointestinal</i> :Gastritis; Inhalation-Rat LC50 • 39000 mg/m ³ 4 Hour(s); Inhalation-Human TCLo • 200 ppm; <i>Behavioral</i> :Somnolence (general depressed activity); <i>Behavioral</i> :Antipsychotic; <i>Behavioral</i> :Irritability; Skin-Rabbit LD50 • 12300 µL/kg; Irritation: Eye-Rabbit • 86 mg • Mild irritation; Skin-Rabbit • 100 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Rabbit TCLo • 10000 mg/m ³ 2 Hour(s) 24 Week(s)-Intermittent; <i>Lungs, Thorax, or Respiration</i> :Acute pulmonary edema; <i>Blood</i> :Hemorrhage; <i>Blood</i> :Changes in leucocyte (WBC) count

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012•No data available
Serious eye damage/Irritation	OSHA HCS 2012•Eye Irritation 2
Acute toxicity	OSHA HCS 2012•Acute Toxicity - Oral 4 - ATEmix(orl) = 1602.73 mg/kg
Aspiration Hazard	OSHA HCS 2012•Aspiration 1
Carcinogenicity	OSHA HCS 2012•Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012•Germ Cell Mutagenicity 1B
Skin corrosion/Irritation	OSHA HCS 2012•Skin Irritation 2
Skin sensitization	OSHA HCS 2012•No data available
STOT-RE	OSHA HCS 2012 •Specific Target Organ Toxicity Repeated Exposure 1; Specific Target Organ Toxicity Repeated Exposure 2
STOT-SE	OSHA HCS 2012 •Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	OSHA HCS 2012•Toxic to Reproduction 1B

Potential Health Effects

Inhalation

Acute (Immediate) Chronic (Delayed)	 May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death. No data available
Skin Acute (Immediate) Chronic (Delayed)	Causes skin irritation.No data available
Eye Acute (Immediate) Chronic (Delayed) Ingestion	Causes serious eye irritation.No data available

- Acute (Immediate)
 - Harmful if swallowed. Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

Chronic (Delayed) No data available

Other

Chronic (Delayed) CNS depression has been reported to occur in chronic abusers exposed to high levels of toluene. Symptoms include drowsiness, ataxia, tremors, cerebral atrophy, nystagmus (involuntary eye movements), and impaired speech, hearing, and vision. Neurobehavioral effects have been observed in occupationally exposed workers. Chronic exposure to benzene, a component of this material, results primarily in hematotoxicity, including aplastic anemia, pancytopenia, or any combination of anemia, leukopenia, and thrombocytopenia Chronic benzene exposure is associated with an increased risk of leukemia. Chronic exposure of workers to naphthalene has been reported to cause cataracts and retinal hemorrhage. Hexane may have effects on the central nervous system and especially peripheral nervous system, resulting in polyneuropathy. Exposure to relatively low concentrations of ethylbenzene for several days to weeks resulted in potentially irreversible damage to the inner ear and hearing of animals.

Mutagenic Effects Repeated and prolonged exposure may cause mutagenic effects.

Carcinogenic Effects • Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects					
	NTP				
1-Methylethylbenzene	98-82-8	Not Listed	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen	
Benzene	71-43-2	Specifically Regulated Carcinogen	Group 1-Carcinogenic	Known Human Carcinogen	
Benzine (motor fuel)	86290-81-5	Not Listed	Group 2B-Possible Carcinogen	Not Listed	
Ethylbenzene	100-41-4	Not Listed	Group 2B-Possible Carcinogen	Not Listed	
Naphthalene	91-20-3	Not Listed	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen	

Reproductive Effects • Repeated and prolonged exposure may cause reproductive effects.

Key to abbreviations

LC = Lethal Concentration LD = Lethal Dose TC = Toxic Concentration TD = Toxic Dose

Section 12 - Ecological Information

Toxicity

• Non-mandatory section information about this substance not compiled for this reason.

Persistence and degradability

• Non-mandatory section information about this substance not compiled for this reason.

Bioaccumulative potential

• Non-mandatory section information about this substance not compiled for this reason.

Mobility in Soil

Non-mandatory section information about this substance not compiled for this reason.

Other adverse effects

• Non-mandatory section information about this substance not compiled for this reason.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	UN1203	Gasoline, Flammable Liquids n.o.s.	3	II	NDA

Special precautions for user

• None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

• Acute, Chronic, Fire

Inventory			
Component	CAS	TSCA	
1,2,4- Trimethylbenzene	95-63-6	Yes	
1- Methylethylbenzene	98-82-8	Yes	
Benzene	71-43-2	Yes	
Benzine (motor fuel)	86290-81- 5	No	
Cyclohexane	110-82-7	Yes	
Ethylbenzene	100-41-4	Yes	
Hexane	110-54-3	Yes	
Naphthalene	91-20-3	Yes	
Toluene	108-88-3	Yes	
Xylene	1330-20-7	Yes	

United States

Labor

U.S OSHA - Process Safety Management - Highly Hazardous Chemicals		
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed

ventional Gasoline		
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S OSHA - Specifically Regulated Chemicals	00200 01 0	Not Listed
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	5 ppm STEL (See 29 CF 1910.1028, 15 min); 0.5 Action Level; 1 ppm TW
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
vironment	00230-01-0	
VIronment U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
•Naphthalene	91-20-3	
•1-Methylethylbenzene	98-82-8	
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	(listed under Ethyl benze
•		(listed under Ethyl benze
•Toluene	108-88-3	
•Xylene	1330-20-7	(isomers and mixtures)
•Benzene	71-43-2	(including Benzene from gasoline)
•Hexane	110-54-3	
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel) U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities	86290-81-5	Not Listed
•Naphthalene	91-20-3	100 lb final RQ; 45.4 kg RQ
•1-Methylethylbenzene	98-82-8	5000 lb final RQ; 2270 k final RQ
•Cyclohexane	110-82-7	1000 lb final RQ; 454 kg RQ
•Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg RQ
•Toluene	108-88-3	1000 lb final RQ; 454 kg RQ
•Xylene	1330-20-7	100 lb final RQ; 45.4 kg RQ
•Benzene	71-43-2	10 lb final RQ (received adjusted RQ of 10 lbs ba on potential carcinogenia in an August 14, 1989 fir rule); 4.54 kg final RQ (received an adjusted RQ 10 lbs based on potentia carcinogenicity in an Aug 14, 1989 final rule)
•Hexane	110-54-3	5000 lb final RQ; 2270 kg final RQ
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
.,_,	86290-81-5	Not Listed
•Benzine (motor fuel)	00230-01-0	NUL LISIGU
•Benzine (motor fuel)		
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities	01 20 2	Not Listed
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities •Naphthalene	91-20-3	Not Listed
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities	91-20-3 98-82-8 110-82-7	Not Listed Not Listed Not Listed

Format: GHS Language: English (US) OSHA HCS 2012

conventional Gasoline		
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	95-05-0 86290-81-5	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs	00290-01-5	NOL LISIEU
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	95-05-0 86290-81-5	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs	00290-01-5	NOL LISTER
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	95-05-0 86290-81-5	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting	00290-01-5	NOL LISIEU
	01 00 0	0.1 % de minimis
•Naphthalene	91-20-3	concentration
•1-Methylethylbenzene	98-82-8	1.0 % de minimis
· ····································		concentration
•Cyclohexane	110-82-7	1.0 % de minimis concentration
•Ethylbenzene	100-41-4	0.1 % de minimis concentration
Teluere	400.00.0	1.0 % de minimis
•Toluene	108-88-3	concentration
•Xylene	1330-20-7	1.0 % de minimis
Ayono	1000 20-1	concentration
•Benzene	71-43-2	0.1 % de minimis
		concentration
•Hexane	110-54-3	1.0 % de minimis concentration
1 0 4 Trimethylhonzone	05 62 6	1.0 % de minimis
•1,2,4-Trimethylbenzene	95-63-6	concentration
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing	04.00.0	
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
	74 40 0	Not Listed
•Benzene	71-43-2	
•Benzene •Hexane	110-54-3	Not Listed
•Benzene •Hexane •1,2,4-Trimethylbenzene	110-54-3 95-63-6	Not Listed Not Listed
•Benzene •Hexane	110-54-3	Not Listed

Format: GHS Language: English (US) OSHA HCS 2012

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

U.S California - Proposition 65 - Carcinogens List		
•Naphthalene	91-20-3	carcinogen, initial date 4/19/02
•1-Methylethylbenzene	98-82-8	carcinogen, initial date 4/6/10
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	carcinogen, initial date 6/11/04
•Toluene •Xylene	108-88-3 1330-20-7	Not Listed Not Listed
•Benzene	71-43-2	carcinogen, initial date 2/27/87
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S California - Proposition 65 - Developmental Toxicity	04.00.0	
Naphthalene 1-Methylethylbenzene	91-20-3 98-82-8	Not Listed Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	developmental toxicity, initial date 1/1/91
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	developmental toxicity, initial date 12/26/97
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	04.00.0	NI-CITATE I
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene •Cyclohexane	98-82-8 110-82-7	Not Listed Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	7000 µg/day MADL (level
		represents absorbed dose)
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	24 μg/day MADL (oral); 49 μg/day MADL (inhalation)
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
Benzine (motor fuel) Security California Bronacition 65 No Significant Bick Loyale (NSBL)	86290-81-5	Not Listed
U.S California - Proposition 65 - No Significant Risk Levels (NSRL) •Naphthalene	91-20-3	5.8 µg/day NSRL
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	54 μg/day NSRL (inhalation); 41 μg/day NSRL (oral)
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	6.4 μg/day NSRL (oral); 13 μg/day NSRL (inhalation)
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
paration Date: 06/November/2015 Page 15 of 16	Format: Ch	19 Language: English (LIS)

Preparation Date: 06/November/2015 Revision Date: 23/November/2015

Page 15 of 16

Format: GHS Language: English (US) OSHA HCS 2012

•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
•Naphthalene	91-20-3	Not Listed
•1-Methylethylbenzene	98-82-8	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	male reproductive toxicity, initial date 12/26/97
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

Revision Date Preparation Date

23/November/201506/November/2015

Disclaimer/Statement of Liability

• The information herein is given in good faith but no warranty, expressed or implied, is made.

Key to abbreviations NDA = No Data Available